

Crommelins Drive Unit



[Main](#)
[More Info](#)
[Manuals](#)
[Brochures](#)
[Safety](#)
[Accessories](#)
[Gallery](#)

2" Crommelins Aluminium Submersible Flexible Drive Pump

Alluminium pump casing



Model Number	FP2TA
Inlet (inch)	2"
Outlet (inch)	2"
Total Head (m)	29m
Volume max. (L/min)	933
Volume max. (L/hr)	56,000
Maximum suction lift (m)	N/A
Pump Type	Aluminium
Suction Type	Self Priming
Impeller	Single
Dimensions (LxWxH)	6m length
Package (LxWxH)	1000x770x200mm
Weight (kg)	31kg
Manufacturers Warranty	12 months



2" Crommelins Aluminium Submersible Flexible Drive Pump
 The FP2TA Flex. Pump is a very popular heavy duty 50mm (2") industrial pump with large 15mm core dry cable which provides wider access and easier flow.

It is made with aluminium alloy casing with wide passages to allow debris (up to 25mm) to pass through and can allow fluids containing up to 60% solids. The main shaft is made from corrosion resistant high quality 316 stainless steel.

Attached to a Drive Unit, these pumps will do a variety of jobs in agricultural, construction and mining applications.

Features

- Aluminium casing
- No suction hose required
- Quick action flexshaft coupling with 3 dog drive
- Includes adaptor for cam lock and discharge hose
- 6m length
- ROPE NOW INCLUDED - Use the rope to lift the pump in and out of holes correctly
- MOVABLE SPIRAL SECTION - Supports the cable when draping over sharp hole lips to prevent kinking

Applications

- Footings
- Manholes
- Tanks
- Drainage
- Pool excavations
- Waste transfer
- Water transfer