

Crommelins Fire Fighting Pump



[Main](#)
[More Info](#)
[Manuals](#)
[Brochures](#)
[Safety](#)
[Accessories](#)
[Gallery](#)
[Video](#)

6.0hp Crommelins Twin Impeller FF Pump

Petrol, twin impeller



6.0hp Crommelins Twin Impeller FF Pump

The Twin Impellor, petrol 6.0hp Fire Fighter Pump provides similar volumes of water to their Single Impeller cousins, but at a far greater pressure.

Used extensively on boom sprays, wash down points and where ever higher pressure water is required. This model is popular due to its reliability, durability and versatility and is also ideal for firefighting, water transfer, washing down farm machinery and many other jobs that require water.

This model will give you top performance when you need it!

The Pump is cast aluminium alloy that comes with a 40mm (1 1/2") inlet and three way outlet - Consisting of 1x 40mm (1 1/2") outlet and 2 x 25mm (1") outlets). There is also 2" Inlet and Outlets available upon request.

Features

- The cast aluminium impeller/s gives improved life
- Self-priming after initial prime
- Bolt on replaceable suction port so enabling easy and quick replacement if inlet cracked or thread is damaged
- Cast iron diffuser increases pump life and greatly reduces maintenance
- Metal (not plastic) delivery outlet caps
- High quality cast aluminium pump body, for longer life and less maintenance.
- Spark arrestor muffler
- Double fuel filter system to protect engine from any water or impurities
- A serviceable carburettor, not a "throw-away", reduces costs
- Double ball bearing crankshaft, increasing engine life
- Pointless ignition system, requires less maintenance, easier starting and more

Model Number	150HPROHCT
Inlet (inch)	1.5"
Outlet (inch)	1x 1.5" and 2x 1"
Total Head (m)	90m
Volume max. (L/min)	300
Volume max. (L/hr)	18,000
Maximum suction lift (m)	8m
Pump Type	Alluminium
Suction Type	Self Priming
Impeller	Twin
Axle Seal Material (Mechanical Seal)	Ceramic-carbon
Engine Make	Subaru
Engine Type	6.0hp EX17
Starting System	Recoil Start
Fuel Type	Petrol
Fuel Tank (L)	3.6L
Noise Level (dB @ 7m)	66db
Package (LxWxH)	510 x 440 x 440
Weight (kg)	30kg
Manufacturers Warranty	2 years
Engine Warranty	3 years



Applications

- Fire fighting
- Water transfer
- Washing down farm machinery
- Boom Sprays
- Water Sprinkling
- Water Tanks
- Rural Properties

Authorised Dealer of:

CROMMELINSTM
 PRODUCTS

www.crommelins.com.au

SUBARU

Industrial
 Power
 Products