



SPITWATER[®]
INDUSTRIAL CLEANING & HEATING EQUIPMENT



SPITWATER[®]
INDUSTRIAL CLEANING & HEATING EQUIPMENT

SW201 - HOT/COLD WATER CLEANER

SPECIFICATIONS

3000 P.S.I. (200 Bar) Pump Pressure
3825 P.S.I. Turbo Pressure (Optional)
15 Litres per minute Pump Volume
415 Volt 7.5 H.P. Electric Motor
1450 RPM Industrial Machine
Temperatures up to 90°

STANDARD EQUIPMENT

10 Metres High Pressure Hose
Insulated On/Off Pistol Assembly
Double Lance Assembly
High and Low Pressure Mode
Adjustable Chemical Injector with Bottle
Operators and Parts Manuals
Bypass Shutdown Timer

<u>FEATURES</u>	<u>BENEFITS</u>
Interpump with Ceramic Pistons and Brass Head	→ Anodised crankcase and oversized bearings → Longer pump life, non corrosive pump head
Water By-Pass Cooling Tank	→ Reduces potential damage to the pump in bypass
Inlet Water Filter	→ Stops debris from scoring pistons and seals
Pressure Gauge	→ Easily monitor pump performance
Powder Coated Zinc Annealed Chassis	→ Resistant to corrosion
Adjustable thermostat for hot water temperature control	→ Set the ideal temperature for any application
Bypass Shutdown Timer	→ Increases life of the machine by shutting down when not in use